

## DECLARATION OF PERFORMANCE: N° 001CPR2013-07-14

1. Identification of the product: **Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5\%$**
2. Intended use: **for internal and external walls and floorings**
3. Name and contact of the manufacturer: **Italcer SpA, via Emilia Ovest 53/A - 42048 Rubiera (RE) – Italia**
4. System of assessment and verification of constancy of performance (AVCP): **System 4**
5. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire</b>	A1 <sub>FL</sub>	EN 14411
<b>Release of dangerous substances, for:</b> - Cadmium - Lead	NPD	
<b>Breaking strength</b>	Thickness $\geq 7.5\text{mm}$ : $\geq 1300\text{N}$ Thickness $< 7.5\text{mm}$ : $\geq 700\text{N}$	
<b>Slipperiness</b>	NPD	
<b>Tactility</b>	NPD	
<b>Thermal shock resistance</b>	Pass	
<b>Durability for:</b> -internal use: -external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer by:

  
 Graziano Verdi  
 Amministratore Delegato

Rubiera, 02/07/2019

## DECLARATION OF PERFORMANCE: N° 003CPR2013-07-14

1. Identification of the product: **Dry-pressed ceramic tiles, with water absorption  $E_b > 10\%$**
2. Intended use: **for internal walls**
3. Name and contact of the manufacturer: **Italcer SpA, via Emilia Ovest 53/A - 42048 Rubiera (RE) – Italia**
4. System of assessment and verification of constancy of performance (AVCP): **System 4**
5. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
<b>Reaction to fire</b>	A1 <sub>FL</sub>	EN 14411
<b>Release of dangerous substances, for:</b> - Cadmium - Lead	NPD	
<b>Breaking strength</b>	Thickness $\geq 7.5\text{mm}$ : $\geq 600\text{N}$ Thickness $< 7.5\text{mm}$ : $\geq 200\text{N}$	
<b>Slipperiness</b>	NPD	
<b>Tactility</b>	NPD	
<b>Thermal shock resistance</b>	Pass	
<b>Durability for:</b> -internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 5.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and behalf of the manufacturer by:



Graziano Verdi

Amministratore Delegato

Rubiera, 21/05/2021